



EN:61326-1



■ UT341



■ UT342

### SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT341	UT342
<b>Model</b>		<b>UT341</b>	<b>UT342</b>
Iron Matrix Measure	0µm~55µm 56µm~1000µm	±3dgt ±(3.0%+1dgt)	±3dgt ±(3.0%+1dgt)
Aluminum Matrix Measure	0µm~55µm 56µm~1000µm		±3dgt ±(3.0%+1dgt)
Resolution	1µm	✓	✓
<b>Features</b>			
Display Count		10000	10000
Auto Power Off		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
MAX/MIN		✓	✓
Data Logging		2000	2000
LCD Backlight		✓	✓
Measurement Mode	Continuous or Single Measurement	✓	✓
Key Mis-press Buzzer		✓	✓

### GENERAL CHARACTERISTICS

Power	9V Alkaline Battery (6LF22)
LCD Size	22mm × 22mm
Product Color	Red and Grey
Product Net Weight	144.2 g
Product Size	153mm × 110mm × 40mm
Standard Accessories	UT341-Battery, Standard Membrane Slice, Iron Matrix Slice, Carrying Bag UT342-Battery, Standard Membrane Slice, Iron Matrix Slice, Aluminum Matrix Slice, Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	530mm × 485mm × 320mm (0.082 CBM Per Standard Carton)
Standard Carton Gross Weight	9.5 Kg